





REVISION	DESCREPTION	DATE	APPD
0	SET UP	SEP/19/2000	C.Y.LIN

2570-□□T - 1
POLARIZING PEGS

2570-□□T



Dimension (mm)									
Position	A ± 0.20	B ± 0.20	B1 ± 0.15	B2 ± 0.15	C ± 0.20	D ± 0.20	E ± 0.20	E1 ± 0.15	E2 ± 0.15
20	5.08	15.24	13.65	9.25	16.70	5.08	15.24	13.65	9.25
28	7.62	17.78	16.19	11.79	20.30	7.62	17.78	16.19	11.79
32	7.62	17.78	16.19	11.79	22.50	10.16	20.32	16.73	14.33
44	12.70	22.86	21.27	18.87	27.50	12.70	22.86	21.27	16.87
52	15.24	25.40	23.81	19.41	31.10	15.24	25.40	23.81	19.41
68	20.32	30.82	28.89	24.49	38.60	20.32	30.82	28.89	24.49
84	25.40	35.90	33.97	29.57	45.50	25.40	35.90	33.97	29.57

MATERIAL

Insulator Material : PPS & 40% Glass Fiber (UL 94V-0)
 Contact Resistance : 30 MΩ MAX at DC 100MA
 Insulator Resistance : 1000 MΩ Min at DC 500 V
 Current Rating : 1AMP
 Dielectric Withstanding Voltage : AC 500V FOR 1 minute
 Temperature Rating : -55°C ~ +105°C
 Contact Material : Phosphor Bronze Tin Plated
 0 : WITHOUT POLARIZING PEGS
 1 : WITH POLARIZING PEGS

UNIT : mm



HO CHIEN ENTERPRISE CO. LTD

TITLE :

2570-PLCC SURFACE MOUNTING

DR :

RON CHEN

CHK :

J.T.CHEN

APPD :

C.Y.LIN

PAGE :

1 OF 1

HO CHIEN P/O NO.

2570-□□T