

Product	STD Rectifier Diodes	Type	GPC12603-4-01-3RD								
Metallization	<p>Top Al ①</p> <p>Bottom Ag ②</p>										
Dimension in mils	<table border="1"> <thead> <tr> <th></th> <th>Dimension</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>50±1</td> </tr> <tr> <td>B</td> <td>26.8±2</td> </tr> <tr> <td>D</td> <td>10.3±0.5</td> </tr> <tr> <td>E</td> <td>1.5.±1</td> </tr> </tbody> </table>				Dimension	A	50±1	B	26.8±2	D	10.3±0.5
	Dimension										
A	50±1										
B	26.8±2										
D	10.3±0.5										
E	1.5.±1										

Absolute Maximum Ratings (Ta=25°C)

PEAK REVERSE VOLTAGE VRM .. 300 V
 FORWARD SURGE CURRENT IFSM....30 A STORAGE TEMPERATURE RANGE Tstg .. -65~150°C

Electrical Characteristics

Item	Symbol	Test Condition	Standard
FORWARD VOLTAGE(for axial type)	VF	IF=1A	0.98 V (MAX)
REVERSE CURRENT	IR	VR=300V	3μA (MAX)
BREAKDOWN VOLTAGE	BVR	IR=5μA	360V (MIN)

Quality Yield Assurance per die: 100%