


PCB LAYOUT
(Top View)



SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20M-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char. RoHs Compliant

- Housing : Nylon (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze
- Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

HC-019-1SMD-F-X

F=8p8c

Gold plated	1=15u, 3=50u 2=30u, 4= 6 u
-------------	-------------------------------

HO CHIEN
www.hochien.com

TITLE
RJ11 or RJ12 S.M.T Mounting Side Entry Jack
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-019-1SMD-F-X

SCALE SIZE DWG. NO. 9754 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	CK'D Johnn JAN-12 '05
	ANGLE+0°30'	RADIL	+0.45 -0.15	APP'D Rlliv JAN-12 '05	

DWG. NO.

AS019014