

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
 Color : Black Color
 Spring Wire : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 40°C / +85°C
 Durability : 500 Mating cycles Min.

HC-040SH4 FXA3N1

NUMBER OF PORT

F=8p8c

Gold plated
1=15u , 3=50u
2=30u , 4= 6 u

HO CHIEN





www.hochien.com

TITLE

1x4 8POSITIONS
 SIDE ENTRY SHIELDED PCB GANG JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-040SH-4-F-LX-A3-N1

SCALE SIZE DWG. NO. 9638-S SERIES



PCB LAYOUT
 (Top View)

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	DR. <i>Steven</i> CK D <i>John</i> APP'D <i>Billy</i>	MAR-01 '06
	ANGLE	°/30'	RADL		MAR-01 '06
			+0.45 -0.15		MAR-01 '06

DWG. NO.

AS040019-1