


**PCB LAYOUT
(Top View)**



SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.

Contact Resistance : 20milli-Ohm Max.

Rating Current : 1.5A Max.

Rating Voltage : 120V AC.

Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)

Color : Black Color

Spring Wire : 0.45mm Dia. Phosphor bronze
Gold Plating Over Nickel.

Temperature Range : - 25 / +80 Deg C

Durability : 500 Mating cycles Min.

HC-032-6-X-X

B=6p2c, C=6p4c
D=6p8c

Gold plated 1=15u, 2=30u
3=50u, 4= 6 u

HO CHIEN

www.hochien.com

TITLE

LOW PROFILE PCB MOUNT SIDE ENTRY JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-032-6-X-X

SCALE SIZE DWG. NO. 9682 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. Steven	DATE JAN-12 '05
 THIRD ANGLE PROJECTION	LINEAR	0.0010 0.0005 0.0002	0.0254 0.0127 0.0050	CK D Johnn	JAN-12 '05
	ANGLE	±0.50 INCH	±0.13 MM	APP D Bliffy	JAN-12 '05

DWG. NO.

AS032002