



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISOR	APPD

Note:

1. Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass, t=0.25mm.
- 1.3 Shell: Cold rolled steel, t=0.30mm.

2. Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3. Finishes:

- 3.1 Contacts: Gold flashed 1u", 3u", 5u", 10U", 15u", 30u".
- 3.2 Shell: Nickel, tin plated

3	Shell	1	Cold Rolled Steel	T=0.30mm	Nickel Plated
2	Contact	4	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/White
No.	Part Name	Q'ty	Material	Remarks&Thickness	Finish

PART NO:		MATERIAL:		<b>HO CHIEN</b> <a href="http://www.hochien.com">www.hochien.com</a>	
MODEL NO:		FINISH:			
UNIT: mm	SIZE: A4	COLOR:		PART NAME:	
TOLERANCE UNSPECIFIED		DR: 黃義強 '06/04/05		USB-A公焊線式短鐵殼	
.x	±0.30	CHK: Kevin '06/04/05		DWG NO: 275	
.xx	±0.20	APP: Kent '06/04/05		SCALE: 3:1	
.xxx	±0.10			SHEET: 1 of 1	
ANG.	±1°			REV: A0	