



NOTE :

1. MAXIMUM ELECTRIC CURRENT :

A.W.G.	22	20	18
AMP.	3	4	7
2. MAXIMUM ELECTRICAL RATING : 105°C 300 VOLTS MAX.
3. INSULATION MATERIAL : NYLON
4. INSULATION COLOR : RED
5. TERMINAL MATERIAL : BRASS
6. WIRE RANGE : 22-18 A.W.G. (0.5-0.75 mm²)
7. NEMA TAB : 0.032 inch * 0.250 inch (0.8 mm * 6.35 mm)
8. TERMINAL SURFACE TREATMENT : TIN PLATED
9. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ± 0.20	ANGLE
6 > 18 mm ± 0.30	0° > ° REF ±
18 > 30 mm ± 0.40	° > ° ±
30 > 75 mm ± 0.50	° > ° ±

NAME	METAL STRIP TYPE NYLON-INSULATED FLAG FEMALE DISCONNECTORS (MS SERIES)				UNIT	mm	
PART NO.	FLDNY1-250A-MS	MATERIAL	FLDNY1-250A-MS	APPROVE			
NUMBER	KA-95057-C -EA462A	SCALE	SHEET	PAGE	CHECKED		
DATE	2006/02/06	3/1	1-0	10F2	DRAWN	張馨尹	

HO CHIEN