



**ELECTRICAL CHARACTER:**

1. 100 % OPEN&SHORT TESTING
2. WITHSTANDING VOLTAGE:DC 300V 0.1Sec
3. INSULATION RESISTANCE:10M Ohms(Min)
4. CONDUCTIVE RESISTANCE:3 Ohms(Max)

|    |           |                                                                             |      |
|----|-----------|-----------------------------------------------------------------------------|------|
| ④  | TERMINAL  | AMP pitch:4.2mm Brass Tin Plated Terminal SOCKET #22-18AWG Wire Local FL-PT | 2Pcs |
| ③  | HOUSING   | AMP pitch:4.2mm 2P Nylon Color:White FEMALE Housing Local FL-2RF            | 1Pcs |
| ②  | WIRE      | UL1015 600V 105°C 22AWG OD:2.4mm COLOR:BLACK                                | 1Pcs |
| ①  | WIRE      | UL1015 600V 105°C 22AWG OD:2.4mm COLOR:RED                                  | 1Pcs |
| NO | PART NAME | SPECIFICATION                                                               | Q'TY |

|       |                          |  |           |                    |            |
|-------|--------------------------|--|-----------|--------------------|------------|
| A0    | New Drawing For Approved |  | DATE      | APPVL. BY          | ECO(N) NO. |
| REV.  | DESCRIPTION              |  | DATE      | APPVL. BY          | ECO(N) NO. |
| UNIT  | MM                       |  | TOLERANCE | XX.<br>X.X<br>X.XX | DRAW. BY   |
| SCALE | NONE                     |  |           |                    | CHECKED    |
| SHEET | 1/1                      |  |           |                    | APPVL. BY  |

**Ho Chien**  
www.hochien.com

**8.5" WIREHARNESS W/ 0.375" STRIP**

P/N NO.

CA-B6019-0004

DWG NO.

DWG NAME