



1. ELECTRICAL CHARACTER:

- a. 100 % OPEN&SHORT TESTING
- b. WITHSTANDING VOLTAGE:DC 300V 0.1Sec
- c. INSULATION RESISTANCE:10M Ohms(Min)
- d. CONDUCTIVE RESISTANCE:3 Ohms(Max)

2.PACKAGING:

20PCS/POLY BAG +LABEL

Description:11" WIREHARNESS,18-22AWG
 Ho Chien P/N:CA-B8155-0004
 QTY:20 PCS

3.THE ASSEMBLY REQUIREMENTS TO BE COMPLY WITH LATEST IPC/WHMA-A-620 STANDARD

⑤	TERMINAL	Molex 19002-0009 Red Nylon (Tab:4.75*0.81mm) Fully Insulated Quick Disconnect Female For 18-2 AWg Wire Local FDFN1.25-187D(8)	2PCS
④	TERMINAL	Molex 1602-0086 Pitch:2.54mm Brass Tin Plated #22-#24 Wire Local A2541-Tbe	2PCS
③	HOUSING	Molex 5057-9402 Pitch:2.54mm 2Pos PBT Black with Lock Housing Local A2541H-M-2P	1PCS
②	WIRE	UL1007 300V 80°C 22AWG OD:1.6mm WIER COLOR:RED	1PCS
①	WIRE	UL1007 300V 80°C 22AWG OD:1.6mm WIER COLOR:BLACK	1PCS
NO	PART NAME	SPECIFICATION	Q'TY

REV.	DESCRIPTION		DATE	APPVL. BY	ECO(N) NO.
UNIT	MM	TOLERANCE XX. X.X X.XX ANGLE ±0.5°	DRAW. BY		
SCALE	NONE		CHECKED		
SHEET	1 / 1		APPVL. BY		

Ho Chien
www.hochien.com

DWG
NAME

11" WIREHARNESS,18-22AWG
CA-B8155-0004

PAGE NO.

1 / 1

P/N NO.

CA-B8155-0004