


**SCHEMATIC**



- SPECIFICATION**
1. Rating : DC 50V 0.5A;
  2. Contact resistance:  $\leq 0.03\Omega$ ;
  3. Insulation resistance:  $\geq 100M\Omega$  (DC250V);
  4. Withstand voltage: 500VAC ;
  5. Insertion and extraction force: 3-15N;
  6. Life test: 5,000 cycles.

6	HOUSING	1	P A66					
5	AXIS SUPPORT	1	BRASS					Ni-Plating
4	PIN	1	H59 BRASS					Ni-Plating
3	SPRING	1	BRONZE					Cu-Sn-Plating
2	CURVE PIECE	1	H62 BRASS					Cu-Sn-Plating
1	FLAT PIECE	1	H62 BRASS					Cu-Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL					PLATING
UNIT:MM		TYPE:	MODEL NO:					
DC JACK			DC-025M					
DESIGNERBY:	LUDI							
CHECK BY:	QJ							
APPROVED	XJX							
				PAPER NO: A4	PAGE 1 OF 1			
TOLERANCES		ANGLES	SCALE	VER				
±0.15		±1.5°	3:1	1				

**HO CHIEN**  
www.hochien.com